



WATER-COOLED DELTA STAR HEAT PUMP SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH	VOLTS / PHASE	AMPS.	WATTS	L	W	H	WO	REFRIGERANT TYPE/CHARGE	* CITY WATER USE RANGE WITH 65°F EWT 5°F ΔT MAX(GPM)	PROCESS WATER FLOW RANGE (GPM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
DSHP-7WC	3/4	9500	115	13	1495	27"	22"	16"	10"	R134A / 2 Lbs. 6 oz	4	15-30	112	150	33x26x23
DSHP-8WC	3/4	9500	230/1	7	1610	27"	22"	16"	10"	R134A / 2 Lbs. 6 oz	4	15-30	112	150	33x26x23
DSHP-9WC	1	12,000	230/1	7.2	1656	27"	22.5"	16"	10"	R134A / 3 Lbs.	5	20-35	117	160	33x26x23
DSHP-10WC	1 1/2	21,000	230/1	9.5	2185	31"	26"	19"	13"	NU-22 / 4 Lbs.	9	25-40	147	250	36x33x24

* CITY WATER USE BASED ON 55-60°F WATER TEMPERATURE ENTERING THE UNIT. WATER FLOWS THROUGH UNIT ONLY WHEN THE UNIT IS RUNNING. IN THE CHILLING MODE THE WATER GPM USE IS ON THE LOW END AND IN THE HEATING MODE THE GPM USE IS ON THE HIGH END. MAKE SURE THE WATER SUPPLY THE RECOMMENDED GPM ON HIGH END OR HIGHER.

ALL DIMENSIONS ARE APPROXIMATE AND CAN CHANGE WITHOUT NOTICE

	Aqua Logic, Inc. 9558 Camino Ruiz San Diego, CA. 92019
	TITLE: DSHP-7WC THUR DSHP-10WC WATER-COOLED DELTA STAR HEAT PUMP SPECIFICATIONS